Oldroyd® Gtx 20 Geotextile Membrane

Product Description

Oldroyd® Gtx 20 Geotextile Membrane is made from polypropylene and is black in colour. The membrane features welded geotextile fleece and 20 mm studs. It is primarily used to protect basement walls and foundations against moisture. It is designed for installation externally. Suitable for use vertically and horizontally.

Accreditations	
CE	SINTEF



Benefits

- Resistant to water and water vapour
- Welded geotextile fleece prevents blockage from fine particles
- Can be used in conjunction with external insulation
- Highly durable
- No maintenance required

Properties

Appearance	Black, moulded polypropylene sheet incorporating raised studs
Size(s) & Packaging	2 × 10 m roll
Coverage	20 m^2
Service Life	For the life of the structure in which it is incorporated
Storage	Cool, dry conditions

Application Information

Preparation

Surface to receive membrane should be sound and structurally stable.

Application

The membrane can either be temporarily fixed to the structure prior to backfill and the weight of the excavated soil will hold the membrane in place. Alternatively, Oldroyd® Gun Plugs can be used to offer a permanent fix to the walls. Please call our technical department for further advice.

Other Information

Oldroyd® Gtx 20 Geotextile Membrane is produced in accordance with ISO 9001 and ISO 14001 quality and environmental management systems.

Oldroyd® Gtx 20 Geotextile Membrane is non-hazardous to the environment.

Redkiln Close,
Horsham,
West Sussex,
RH13 5QL.

T: +44 (0) 1403 210204
F: +44 (0) 1403 217529
E: info@safeguardeurope.com

www.safeguardeurope.com