



COLOURED WOOD PRESERVERS



Application

GUIDELINES



Application Guidelines

What You Will Need









ROXIL® PC COLOURED WOOD PRESERVER

STIFF BRUSH

SANDPAPER

MASKING MATERIALS

PAINT BRUSH

Preparation

Any paint, varnish, dirt or other surface coatings should be removed before application of **Roxil® PC Coloured Wood Preservers**. Sanding may be required to return the wood to a sound surface. Wood should be clean and free from dust, rot and other contaminants. Use a suitable cleaner such as Roxil® 100 Wood and Patio Cleaner. If cleaning with a pressure washer, ensure low pressure is used. Allow 24 hours or more for timber to dry before further treatment. To prevent washing out of the stain before it dries, do not apply if rain is forecast in the next 24 hours. Do not apply if temperatures are forecast to drop below 5 °C.

Test Area

It is recommended to try a small test area before full application to determine compatibility. The final colour of the stain may be affected by type and condition of the wood and may be modified by previous treatments. When using multiple tins, check they share the same batch number to ensure colours match exactly.

Cleaning

When finished, any unused product can be returned to the pack and stored for future use. Clean brushes with warm soapy water. Clean the sprayer by removing residue with a tissue, and then spray through with water to prevent any blockages in the nozzle.

Other Information

Roxil® Wood Protection Cream can be used to over-coat **Roxil® PC** to provide water repellency and increase the lifetime of the stain. **Roxil® PC** is not recommended for cladding over 18 m.

Roxil® PC has been authorised for Use Class 1, 2 and 3.

- Use Class 1: indoor timbers.
- Use Class 2: a situation in which the wood or wood-based product is under cover and not exposed to the weather (particularly rain and driven rain) but where occasional, but not persistent, wetting can occur.
- *Use Class 3:* a situation in which the wood or wood-based product is above ground and exposed to the weather (particularly rain).

Coverage

Coverage rate: 5 m² per litre*

Pack size	Area treated*
1 litre	5 m ²
5 litres	25 m ²

^{*} The coverage rate will vary depending upon the roughness and absorbency of the surface, use as a guide only.

Application Guidelines

Application



Before application, lay down sheeting to protect plants and surrounding areas from splashes or over-spray. It is recommended to cover areas within 3 metres of the area to be sprayed. Do not attempt to spray on a windy day.



For best results, the wood surface should be cleaned before the application.
Roxil® 100 Wood & Patio Cleaner is

recommended. Allow the wood to dry before applying **Roxil® PC**.





Once dry, brush off any dust or debris. Some sanding may also be required, depending on the desired finish. The fence can also be washed down with water, but it must fully dry before application of **Roxil® PC**.





Mask off any areas that are not going to receive the stain such as windows, support posts or door handles. Remove the masking after the stain has fully dried.



Roxil® PC can be applied by large brush. Use a smaller brush for application around details such as shed windows. Apply in 2 – 3 even coats to achieve the desired colour, brushing along the grain. Wait until touch-dry between coats.



Large areas can be coated by electric or hand-pump pressure sprayers. The stains are ready to use – decant directly into the sprayer reservoir.



Roxil® PC is available in handy 1-litre spray bottles – ideal for application in those hard-to-reach places like recesses, trellis work or under eyes.





When spraying **Roxil® PC**, hold the nozzle 15-30 cm from the wood surface and apply in 2-3 even coats for the desired finish. Keep a brush handy to blend in any over-saturated areas, runs or streaks. Wait until touchdry between coats.



can be further protected with Roxil® Wood
Protection Cream

or Liquid. This will limit the damaging effects of water penetration.



COLOURED WOOD PRESERVERS

- Protects against wood rot and decay
- UV-resistant fade-free colours
- Increases lifetime of timber
- Water-based formulation
- Sprayable



Safeguard Europe Ltd

Redkiln Close, Horsham, West Sussex, United Kingdom. RH13 5QL

T 01403 210204 F 01403 217529
E info@safeguardeurope.com
www.safeguardeurope.com
www.roxil.com