

PREPARE PRESERVE PROTECT

# ROXIL<sup>®</sup>

## ENHANCED DECKING OIL



# Application

## GUIDELINES

# Application Guidelines

## What You Will Need



ROXIL® ENHANCED DECKING OIL



ROXIL® 100 WOOD & PATIO CLEANER (RECOMMENDED)



ROXIL® WOOD SCRUB GEL (RECOMMENDED)



PAINT BRUSH AND/OR ROLLER



STIFF WIRE OR NATURAL BRISTLE BRUSHES



HOSEPIPE



SANDPAPER

## Preparation

Before applying **Roxil® Enhanced Decking Oil** make sure that the surface is free from biological growth, **Roxil® 100 Wood & Patio Cleaner** is recommended. To remove heavy grime or grey patina, **Roxil® Wood Scrub Gel** is recommended. Always wash the surface with clean water after either of these cleaning treatments and allow the wood to dry before applying the oil. **Roxil® Enhanced Decking Oil** is recommended for use on pine, larch, cedar and other softwoods. All timber must be clean and free from thick coatings.

## Test Area

It is recommended to try a small test area before full application to determine aesthetic and that the oil penetrates into the surface. The darkening nature of the oil may be affected by type and condition of the wood and may be modified by previous treatments. Generally, expect significant darkening on weathered wood and slight darkening on new wood.

## Maintenance

Although **Roxil® Enhanced Decking Oil** is hard wearing, maintenance will be required to maintain a clean surface. If the colour enhancement fade then an additional application of **Roxil® Enhanced Decking Oil** can be carried out.

## Coverage

Coverage rate: 6 m<sup>2</sup> per litre\*

Pack size	Area treated*
5 litres	30 m <sup>2</sup>

\* Based on the product being applied in two coats. Coverage will vary depending upon the overall porosity of the substrate to be treated, use as a guide only.

## Application

**1**



**SWEEP** **CLEAN** **SCRUB** **RINSE**

Before application, ensure the wood is cleaned as described in the 'Preparation' section. Also brush away any dust or debris with a stiff brush or broom. After cleaning and/or scrubbing, the life of the deck can be increased further by applying Roxil® Wood Preserver, allowing it to dry fully before the oil is applied.



**2**



**3**



**NEW DECKING** **WEATHERED DECKING**



**UNTREATED** **TREATED** **UNTREATED** **TREATED**

Once fully dry, lightly sand/denib the surface with 60- to 100-grit sandpaper to smooth out any surface imperfections. Decant the **Roxil® Enhanced Decking Oil** into a convenient container or tray and begin application. No mixing or shaking is required.

**Roxil® Enhanced Decking Oil** can be applied by brush or roller. Two coats are necessary to get the best protection. *Note: the oil will have a darkening effect on the decking dependant on the type and age of the wood.*

**4**



Once the first coat has been applied, wait until it is touch dry before applying the second coat. The final drying time and that between coats will vary depending on the type of wood and atmospheric conditions. Once dry, **Roxil® Enhanced Decking Oil** will start to provide protection against water ingress and keep it protected. Initial colour enhancement may fade slightly once the coating has dried fully. Apply **Roxil® Enhanced Decking Oil** annually as part of a maintenance regime.

# Roxil<sup>®</sup>

## ENHANCED DECKING OIL

- Enhances the grain and natural colour of wood
- No peeling, blistering or flaking
- Waterproofs and controls mould
- UV protection



**Safeguard Europe Ltd**  
Redkiln Close,  
Horsham, West Sussex,  
United Kingdom. RH13 5QL

**T** 01403 210204    **F** 01403 217529

**E** [info@safeguardeurope.com](mailto:info@safeguardeurope.com)

**[www.safeguardeurope.com](http://www.safeguardeurope.com)**

**[www.roxil.com](http://www.roxil.com)**