

OLDROYD 'P' PlasterMembrane



Cover **damp**, contaminated walls **instantly**.
Then **apply a plaster finish**.



Description

Oldroyd 'P' is a studded polypropylene waterproofing membrane with a special mesh welded to one side. It is fixed to damp, contaminated walls using Oldroyd Plaster Plugs, with the studs facing the wall. This creates an air-gap, which allows the wall to breathe whilst blocking the passage of moisture. On the reverse side of the membrane, the special mesh can be plastered onto, allowing a dry plaster finish to be achieved without risk of contamination from any damp or salts in the wall.

Oldroyd 'P' can also be used on external walls to provide protection against penetrating damp.

Oldroyd 'P' can be used above or below ground, however we recommend that our technical department is consulted before using the product below ground.

Advantages

Oldroyd 'P' Plaster Membrane is especially useful in situations where a damp wall is contaminated by salts or the residue of previous attempts to waterproof the wall (such as bitumen). Unlike cementitious waterproofing products, Oldroyd-P Plaster Membrane can be applied directly to contaminated surfaces with minimal preparation.



OLDROYD

THE ULTIMATE WATERPROOF MEMBRANE SYSTEM

OLDROYD 'P' PlasterMembrane



Application

Oldroyd 'P' is hung vertically on the wall, and is fixed into place using specially designed Oldroyd Plaster Plugs. Joints are sealed using Oldroyd Sealing Tape. A plaster finish* is then applied in accordance with good practice. Detailed application instructions are available on request, or can be downloaded from www.safeguardchem.com.

Dry Lining

As an alternative to a plaster finish, plaster board can be applied directly to Oldroyd 'P' Plaster membrane. The plasterboard is attached to the membrane by applying dabs of bonding compound to the heads of the Oldroyd Plaster Plugs that are used to attach the membrane to the wall. Consideration should also be made to the use of Oldroyd Xv membrane, which can be used in conjunction with dry lining, and requires fewer fixings.

Availability

Oldroyd 'P' Plaster Membrane is available in 2m x 20m rolls (40m²).

NEW Plaster Membrane Kit

A complete kit is now available containing everything you need to cover 7.5m²:

1.5 x 5m roll of Oldroyd P plaster membrane

100 plaster plugs with seal

6m roll of sealing tape



Further Reading

Further information about Oldroyd 'P' Plaster Membrane can be found in the following publications:

Oldroyd Exterior Walls
Oldroyd Interior Walls
Oldroyd Flooring
Oldroyd Tunnels and Arches
Oldroyd P Fixing Instructions

These publications can be downloaded free-of-charge from www.safeguardchem.com



Oldroyd Membranes are distributed in the UK by:



Safeguard Chemicals
Redkiln Close, Horsham,
West Sussex, RH13 5QL.
Tel: 01403 210204
Fax: 01403 217529
Web: www.safeguardchem.com.
E-mail: info@safeguardchem.com

* Certain renovating plasters should not be used, please call our technical department for details of suitable plasters.