


VANDEX PROTECTS CONCRETE SURFACES

APPROVED AND TESTED PRODUCTS:

1504 PART 2: SURFACE PROTECTION SYSTEMS FOR CONCRETE

1504 PART 3: STRUCTURAL AND NON-STRUCTURAL REPAIR

OTHER CE MARKED PRODUCTS



*CE marked products,
secure and correct
for construction*



Vandex



Vandex approved products: CE marked and tested products



Approved products: CE marked				CE according to norm		Other approvals
VANDEX	refer also to Technical Data Sheets	consumption		Crack bridging ability	Permeability to water vapour	Potable water
Surface protection	1504 Part 2: surface protection systems for concrete			Class	Class	
CEMELAST	Elasticized waterproofing slurry, chlorid and CO ₂ barrier	4 – 6 kg/m ²	1504-2	A2	II	✓
CEMELAST WHITE/BLUE	Elasticized inner coating for drinking water, white or blue colour	4 – 6 kg/m ²	1504-2	A2	II	✓
BB 75 E	Elasticized waterproofing slurry, CO ₂ barrier, crack bridging	4 – 6 kg/m ²	1504-2	A3	I	
BB 75 E Z	Elasticized waterproofing slurry, increased resistance, crack bridging	4 – 5 kg/m ²	1504-2	A3	I	
POLYCEM Z	Waterproofing slurry, grey, high increased resistance	3 – 6 kg/m ²	1504-2	n/a	I	✓
				structural	non-structural	
Repair products	1504 Part 3: structural and non-structural repair					
SUPER	Slurry in-depth waterproofing and protection, grey	1 – 1.5 kg/m ²	1504-3		✓	✓
BB 75	Waterproofing slurry, grey	3 – 6 kg/m ²	1504-3	✓		✓
BB WHITE	Waterproofing slurry, white	6 kg/m ²	1504-3	✓		✓
UNI MORTAR 1	Waterproofing and repairing mortar, structural	12 – 24 kg/m ²	1504-3	✓		✓
UNI MORTAR 2	Rapid setting mortar for waterproofing and repairing, screed	12 – 24 kg/m ²	1504-3		✓	
BB 75 Z	Waterproofing slurry, grey increased resistance	3 – 6 kg/m ²	1504-3	✓		✓
UNI MORTAR 1 Z	Waterproofing and repairing mortar, increased resistance, structural	12 – 24 kg/m ²	1504-3	✓		✓
CEMLINE TOP GREY/WHITE	Final protective slurry for drinking water, grey/white	6 – 8 kg/m ²	1504-3		✓	✓
CEMLINE MORTAR	Repair mortar and inner coating for drinking water, structural	12 – 24 kg/m ²	1504-3	✓		✓
CEMLINE MG 4	Repair mortar, fibre reinforced, sprayable, structural	20 – 60 kg/m ²	1504-3	✓		✓
CRS REPAIR MORTAR 05	Repair mortar, general purpose, static	18 kg/m ² per 10 mm	1504-3		✓	
POLYCEM Z MORTAR	Waterproofing and repairing mortar, high increased resistance, PCC	12 – 24 kg/m ²	1504-3		✓	✓
Specialty products	1504 Part 6, 934 Parts 1 and 2, 998 Part 1					
GROUT 04	Grouting material, 0 – 4 mm, 15 – 60 mm voids		1504-6			
REFURBISHMENT PLASTER white	Plastering damp salt contaminated walls	12.5 kg/m ² per 10 mm	998-1			
LEVELLING PLASTER	Levelling uneven substrates and creating salt inclusion zones	13.5 kg/m ² per 10 mm	998-1			
INSULATION PLASTER	Insulating damp salt contaminated walls	7.5 kg/m ² per 10 mm	998-1			

Note

Z: Cement is more sulfat resistant in these products.

The information contained herein is based on our longterm experience and the best of our knowledge. We can, however, make no guarantee since for a successful outcome, all circumstances in an individual case must be taken into consideration. Indications of quantities required are only averages which in certain cases might be greater.

Vandex®

CONCRETE PROTECTION AND WATERPROOFING

An RPM Company

HEADOFFICE AND INTERNATIONAL SALES:
VANDEX INTERNATIONAL LTD
 P.O. Box, CH-4501 Solothurn/Switzerland
 Phone: +41 32 626 36 36, Fax +41 32 626 36 37
 E-mail: info@vandex.com www.vandex.com

PRODUCTION AND SALES GERMANY/AUSTRIA:
VANDEX ISOLIERMITTEL-GESELLSCHAFT m.b.H.
 P.O. Box, 1406, D-21487 Schwarzenbek/Germany
 Phone: +49 4151 89 15-0, Fax +49 4151 89 15 50
 E-mail: info@vandex.de www.vandex.de



VX1FC1110