

# BrickFix DriveTie Fixing Tool

## Product Description

The **BrickFix DriveTie Fixing Tool** is used for the rapid installation of **BrickFix DriveTie Helical Wall Ties**. It is designed to be used in both SDS and SDS Plus hammer drills.

## Benefits

- Quick and easy to use
- Tough and durable design
- Fitted with ergonomic handle for ease of use



## Properties

### Size(s) & Packaging

Fits 8 mm, 9 mm and 10 mm  
DriveTie sizes

## Application Information

### Preparation

Drill a pilot hole in the position required. Attach the **BrickFix DriveTie Fixing Tool** into the SDS chuck. Ensure that the drill is set to hammer action only.

### Application

Insert the **BrickFix DriveTie Helical Wall Tie** into the **BrickFix DriveTie Fixing Tool** and locate into the pre-drilled pilot hole. Allow the hammer action of the drill to drive the tie fully home. The spring action on the tool will allow for the tie to be set 10 mm below the surface.

*Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.*