

Dryzone® Anti-Mould Additive

Product Information

Dryzone® Anti-Mould Additive adds mould-resistance to paints, wallpaper paste and grouts preventing the growth of mould on the dried surface. Ideal for walls and ceilings in private and social housing and a wide range of public and commercial buildings.

Benefits

- Adds mould-resistance to paints, wallpaper pastes and grouts
- Compatible with all types of paint (emulsion, vinyl, silk or matt)
- Prevents the recurrence of black mould
- Compatible with all known paint finishes
- Easy to use and cost effective

Properties

Appearance	Clear liquid	
Size(s) & Packaging	100 ml bottles	
Coverage	Emulsion-based paint	20 ml per litre
	Solvent-based paint	10 ml per litre
	Wallpaper paste	20 ml per litre
	Grout	20 ml per litre
Storage	Store above 5°C in dry conditions. Keep container tightly closed and away from children	
Shelf Life	12 months	

Application Information

Preparation

Preparation is straightforward and very similar to normal good decorative practice.

Remove any loose material such as old paint, grease, dirt, mould or defective wallpaper. **Dryzone® 100 Mould Remover**



can be used for wetting mould-contaminated wallpaper prior to removing it.

1. Make good any defects in the surface and rub down to a smooth finish.
2. Wash and clean all surfaces (walls, ceilings, window frames and joinery) using **Dryzone® 100 Mould Remover**. If necessary clean badly affected areas a second time.
3. Allow to dry thoroughly.
4. If necessary, apply an appropriate primer or sealer to new, unprimed or porous plaster and wooden surfaces or bare metal.

Mixing

Emulsion based paints - vinyl, silk or matt:

Add 100 ml of **Dryzone® Anti-Mould Additive** to 5 Litres. Blend the Anti-Mould Paint Additive until fully dispersed, for at least 1 minute.

Solvent based paints - primer, undercoat or gloss:

Add 50 ml of **Dryzone® Anti-Mould Additive** to 5 Litres. Blend the Anti-Mould Paint Additive until fully dispersed, for at least 1 minute.

Wallpaper paste and Tile grout:

Add 100 ml of **Dryzone® Anti-Mould Additive** to 5 Litres. Blend the Anti-Mould Paint Additive until fully dispersed, for at least 1 minute.

Application

Apply the paint, paste or grout in the normal way according to the manufacturer's instructions.

Do not overcoat the anti-mould finish (or wallpaper over it) as this will effectively seal in the mould-resistant finish and allow the mould to grow back.

If an unfinished, textured wallpaper (blown vinyl, woodchip etc.) or similar is to be used then it should be hung after the **Dryzone¹⁰⁰ Mould Remover** has fully dried. The wallpaper should then be coated with the anti-mould finish as above.

Other Information

Dryzone[®] Anti-Mould Additive will help compliance with Section 82 (Statutory Nuisance), Chapter 43 of the Environmental Protection Act 1990, either used alone or part of various strategies to prevent condensation and mould growth in both private and public tenanted accommodation.

For more information see the Safety Datasheet (SDS).

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.