

# Roxil® Enhanced Decking Oil

## Product Description

**Roxil® Enhanced Decking Oil** is a solvent based oil liquid that enhances the natural colour of pine, larch, cedar and other softwoods. It provides a breathable waterproof surface lining film that can reduce water ingress by up to 75% <sup>[1]</sup>. A biocide is included to protect the film from damage caused by mould. It can be applied by brush or roller.

## Benefits

- Enhances the grain and natural colour of wood
- No peeling, blistering or flaking
- Waterproof

## Properties

Appearance	Straw coloured oily liquid
Density	0.9 g/cm <sup>3</sup>
Size(s) & Packaging	5 litre jerry
Coverage	6 m <sup>2</sup> per litre <sup>[2]</sup>
Storage	Store in a cool dry place. Protect from frost
Shelf Life	12 months

## Application Information

**Roxil® Enhanced Decking Oil** is recommended for use on pine, larch, cedar and other softwoods. All timber must be clean and free from thick coatings. Carry out a test area to check that **Roxil® Enhanced Decking Oil** penetrates into the surface.

## Preparation

Before applying **Roxil® Enhanced Decking Oil** make sure that the surface is free from biological growth. Use an appropriate fungicide/algaecide to clean the surface and allow the wood to dry before applying the coating.

## Application

**Roxil® Enhanced Decking Oil** can be applied by brush or roller. Two coats are necessary to get the desired results. Once the first coat has been applied, wait until it is touch dry



before applying the second coat. The final drying time and that between coats will vary depending on the type of wood and atmospheric conditions. Once dry **Roxil® Enhanced Decking Oil** will start to provide protection against water ingress. Initial colour enhancement may fade slightly once the coating has dried fully.

## Maintenance

Although **Roxil® Enhanced Decking Oil** is hard wearing, maintenance will be required to maintain a clean surface. If the colour enhancement fade then an additional application of **Roxil® Enhanced Decking Oil** can be carried out.

## Other Information

Keep out of reach of children and animals. Unprotected persons and animals should be kept away from treated surfaces until dry. For full health and safety information consult Safety Datasheet (available on request). Always read the label.

**Roxil® Enhanced Decking Oil** is produced in accordance with ISO 9001 and ISO 14001 quality and environmental management systems.

*Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.*

<sup>[1]</sup> Based on laboratory testing on pine

<sup>[2]</sup> Based on the product being applied in two coats. Coverage will vary depending upon the overall porosity of the substrate to be treated.