

SoluGuard® Multi-Surface Biocide

Product Description

SoluGuard® Multi-Surface Biocide is a high-strength biocide for removing algae, fungi, and moss growth on a wide range of surfaces including Internal walls, Plastic, Roof tiles, PVCU, Concrete, Polycarbonate, Brick, Driveways, Stone, Patios, Render, Gravestones and Wood. It is suitable for use in cleaning biological growth from masonry surfaces prior to the application of Stormdry® Masonry Protection Cream. The product can also be used indoors to kill black mould.

This product is not suitable for the treatment of wet rot, dry rot or wood boring insects. Instead, please use SoluGuard® Woodworm & Rot Treatment (BPR).

Benefits

- Ready for use (no mixing required)
- Low VOC (low odour, non-flammable)
- Can be used prior to the application of Stormdry® Cream
- Non-staining

Properties

| | |
|----------------------|--|
| Appearance | Clear liquid |
| Recipe Type | Water-based |
| Density | 1.0 g/cm ³ |
| Size(s) & Packaging | 5 litre jerry cans |
| Coverage | 1 litre covers 2 – 20 m ² . A 5 litre pack covers 10 – 100 m ² . The coverage will vary depending upon the overall porosity of the substrate to be treated. |
| Storage | Store above 5°C in dry conditions in original closed box. Store in a safe place, keep out of reach of children. Keep away from food, drink and animal feedstuffs |
| Shelf Life | 12 months |
| Active Ingredient(s) | Quaternary ammonium compounds (QUATS) (2% w/w) |
| Effective Against | Moulds, algae, lichens and mosses |
| HSE Number | 9517 |
| Re-entry Time | When surfaces are dry |



Application Information

Preparation

When used on exterior surfaces, **SoluGuard® Multi-Surface Biocide** should be applied in dry weather – ideally when no rain is forecast for the next 24 hours.

Application

Apply 1 litre of product per 2 – 20 m² of surface — one 5 litre unit can cover between 10 – 100 m². The coverage will vary depending upon the overall porosity of the substrate to be treated. As a guide for materials such as masonry and patios an application rate of 2 – 10 m² per litre can be expected. For materials such as paint or plastic an application rate of 10 – 20 m² per litre can be expected.

For best results, the treated surface should be cleaned after 72 hours using clean water. Where appropriate a pressure washer can be used. This will remove deposits of dead biological growth from the treated surface.

Other Information

For full health and safety information consult safety datasheet (SDS). This product is approved under the Control of Pesticides Regulations (1986) for use as directed. HSE 9517. Use pesticides safely. Always read the label.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.