

SoluGuard Woodworm Treatment (BPR)

Product Description

For the eradication and prevention of attack by wood-boring beetles. **SoluGuard Woodworm Treatment (BPR)** can be applied to timber by brush or coarse spray.

Benefits

- Full-strength formulation
- Solvent-free
- Highly concentrated
- Extremely stable once mixed
- Targets all life-cycle stages

Properties

Appearance	Pale yellow liquid	
Recipe Type	Water-based	
Density	1.0 g/cm ³	
Size(s) & Packaging	5 litre jerry cans	
Coverage	Preventative	1 litre covers 5 m ² . A 5 litre pack covers 25 m ²
	Curative	1 litre covers 3.3 m ² . A 5 litre pack covers 16.5 m ²
Storage	Store above 5°C in dry conditions in original closed box. Store in a safe place, keep out of reach of children. Keep away from food, drink and animal feedstuffs	
Shelf Life	24 months	
Active Ingredient(s)	Permethrin	
Effective Against	Wood-boring beetles	
HSE Number	10137	
Re-entry Time	At least 1 hour after treatment is completed	



Application Information

Preparation

Any paint, varnish, dirt or other surface coating should be removed before application. Wood should be clean and free from dust and other contaminants. Timber to be treated should be reasonably dry before treatment although the product will penetrate into damp timbers.

Application

Preventative: Apply by brush or coarse low pressure spray onto timber at a rate of 5 m² per litre or to refusal. Apply in 2 - 3 coats depending on wood species and surface characteristics.

Curative: Apply by brush or coarse low pressure spray onto timber at a rate of 3.3 m² per litre or to refusal. Apply in 2 - 3 coats depending on wood species and surface characteristics.

After application tools should be cleaned immediately with warm, soapy water.

Other Information

SoluGuard Woodworm Treatment (BPR) is authorised for use against attack by wood boring insects and prevent re-infestation in use classes 1 and 2.

Use class 1: situation in which the wood or wood based product is inside a construction, not exposed to the weather and wetting.

Use class 2: situation in which the wood or wood-based product is under cover and not exposed to the weather (particularly rain and driven rain) but where occasional, but not persistent, wetting can occur.

SoluGuard Woodworm Treatment (BPR) is touch dry in 1 hour depending on wood and ambient conditions. Unprotected persons and animals should be kept away from treated surfaces for 48 hours or until dry. Low temperatures, increased humidity and ingredients of some wood types may increase drying time. Product should be suitable for over coating 24 hours after application depending on wood and ambient conditions.

This material and its container must be disposed of in a safe way (Hazard waste key: 020108). Do not empty into drains. Do not contaminate ground, waterbodies or watercourses with chemicals or used container.

Certified	Organism	Use	Rate
BS EN 46	House Longhorn Beetle (<i>Hylotrupes bajulus</i>)	Preventative	200 ml/m ²
BS EN 118	Termites (<i>Reticulitermes flavipes</i>)	Preventative	200 ml/m ²
BS EN 1390	House Longhorn Beetle (<i>Hylotrupes bajulus</i>)	Curative	300 ml/m ²
BS EN 370	Common Furniture Beetle (<i>Anobium punctatum</i>)	Curative	300 ml/m ²

Efficacy data for SoluGuard Woodworm Treatment (BPR)

For full health and safety information consult safety datasheet (SDS). This product is approved under the Control of Pesticides Regulations (1986) for use as directed. HSE No.10137. Use pesticides safely. Always read the label.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.