



# Stormdry® EP-Board Adhesive

### **Product Description**

**Stormdry**® **EP-Board Adhesive** is a fast curing foam adhesive for use with Stormdry® EP-Board.

#### **Benefits**

- · Ready to use
- Fast Curing
- · Water Resistant
- · B2 fire rated

### **Properties**

Appearance	Off-white foam adhesive
Sizes(s) & Packaging	750 ml can
Coverage	Up to 15 m <sup>2</sup> per 750 ml
Fire Resistance	Class B2
Application	Straw applied
Storage	Store upright in a cool, well ventilated area. Keep container tightly closed. Protect from frost.
Application Temp	+5 °C minimum to +35 °C maximum

## **Application Instructions**

### Preparation

Shake the can vigorously for 30 seconds then screw the threaded end of the gun or straw onto the valve. During processing, the can must be held inverted with the valve in bottom position. Always wear gloves and protective eyewear when applying **Stormdry**® **EP-Board Adhesive** and ensure surfaces are clean and free from loose particles, oil or grease.



### **Application**

It is recommended to lightly wet the wall surface before application to aid curing of the adhesive and avoid unwanted expansion.

Lay the Stormdry® EP-Board on the ground with the dark-grey aerogel blanket facing up. Apply **Stormdry® EP-Board Adhesive** in a continuous line inset approximately 30 mm from the edge of the board until the entire perimeter has been covered. Infill the remainder of the board with the adhesive in a single wide zig-zag pattern. Pick up the Stormdry® EP-Board, making sure to grip it at the edges, and offer the adhesive covered side up to the wall. Apply gentle pressure and hold the board in place until the adhesive provides enough adhesion to support itself, making sure that the board is level with the wall. Repeat the process with more boards, tiling them across the wall until the wall is completely covered. They can either be staggered or applied in-line.

Please refer to Stormdry® EP-Board Application Guidelines for full details of how to apply.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.

Technical Datasheet Last modified 09/23 1 / 1