

Stormdry® EP-Board Primer

Product Description

Stormdry® EP-Board Primer is a liquid-applied primer to aid adhesion of surface finishes such as paint and plaster to the MgO board.

Benefits

- Ready to use
- Vapour open
- Low odour

Properties

Appearance	White liquid, dries off-white
pH	11.1
Sizes(s) & Packaging	1 litre tin
Coverage	Up to 3.5 m ² per litre
Storage	Protect from frost. Store above 5 °C



- Allow primer 24 hours to cure before applying appropriate plaster finishes
- Clean any splashes and spills immediately.
- Allow to dry completely before further application, plaster coverings or decoration.
- Wash splashes, tools and brushes with water.
- Wear the appropriate Personal Protective Equipment

Please refer to Stormdry® EP-Board Application Guidelines for full details of how to apply.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.

Application Instructions

Preparation

- Thoroughly mix before use
- All surfaces to be primed should be clean, dry and free from dirt, grease, dust or other contaminants.
- Protect surrounding surfaces, particularly glass
- Test a small area for suitability with your specific materials before use

Application

- Stir well before use
- Apply with a broad brush using short strokes. Ensure the grit is evenly spread across the surface